



Vibraquipo, S.L.U.

C/ Gaitero de Soutelo, 3 Bajo.

36.004 Pontevedra (Spain)

Phone: +34 986 860 272

www.vibraquipo.com - vibraquipo@vibraquipo.com



EQUIPMENT FOR BLASTING

Capacitor Blasting Machine AI2600 has 3 different models to fulfill with your blasting requirements.

Lightweight, battery powered and electronically controlled, with a fast charging time and accurate precision over the energy given to the firing circuit in comparison with traditional mechanical blasting machines.

This blasting machine has been designed according to the EN-13763-26 Norm.

TECHNICAL DATA			
	AI-2600/70	AI-2600/140	AI-2600/210
Voltage	2600 V / 1600 V	2600 V / 1600 V	2600 V / 1600 V
Capacitor	70 μ F	140 μ F	210 μ F
Weight	6.4 kg	7.2 kg	8.0 kg
Dimensions	400 x 200 x 320 mm		
Test device	Built-in	Built-in	Built-in
Maximum resistance of the circuit			
Detonator type A 3 mJ/ Ω Voltage: 2600 V	1.800 Ω	1.800 Ω	1.800 Ω
Detonator Type U 16 mJ/ Ω Voltage: 2600 V	800 Ω	825 Ω	850 Ω
Detonator Type HU 2500 mJ/ Ω Voltage: 2600 V	45 Ω	60 Ω	70 Ω

Not valid for use in gassy mines.

Refer to the instruction manual for safety and operating mode.

The documentation described herein shall not be considered as contractual commitment.